



## 3227 Series Tripod Jack 5 Ton Capacity (4.5 tonnes)



The six 3227 Series jacks are designed around a common cylinder, pump and reservoir configuration that is compatible with four tripods. The cylinder, pump and reservoir can be removed from one 3227 Series tripod and installed in another, allowing six roll under heights.

All jacks in the 3227 Series are constructed "better than they have to be", and rigorously tested.

### Standard High Quality Features:

- Steel Reservoir
- Extension screw with adjustable height set by quick release pin
- Durable powder coat finish
- Tilt and roll mobility

### Standard Tests:

- Jack is set to relieve at 110% of rated load
- Structurally tested at a 150% of rated load

### Seal Kits:

- Pump/Reservoir – 324-V-31
- Ram/Cylinder – 324-3227K

SPECIFICATIONS											
P/N	Capacity		Roll Under		Hydraulic Lift		Ext Screw		Total Height		
	(tons)	(tonnes)	(")	(mm)	(")	(mm)	(")	(mm)	(")	(mm)	
3227	5	4.5	30	762	21	533	10	254	61	1549	
3228	5	4.5	32	813	21	533	10	254	63	1600	
3229	5	4.5	36	914	21	533	10	254	67	1702	
3230	5	4.5	44	1118	21	533	10	254	75	1905	
3231	5	4.5	66	1676	21	533	10	254	97	2464	
3232	5	4.5	57	1454	21	533	10	254	88	2242	